



PRODUCT TECHNICAL DATA SHEET

WHITE SPIRIT 205 FBP

TEST	METHOD	UNIT	RESULT
Saybolt Color	ASTM D 156-15	-	+30
Flash Point (Proc. A)	ASTM D 93	°C	39.0
Density @ 15°C	ASTM D 4052	Kg/l	0.7885
Total Sulfur Content	ASTM D 4294	%(m/m)	0.0170
DISTILLATION			
IBP		°C	153.3
10			160.4
20			162.6
30			164.7
40			167.3
50			170.0
60			173.2
70			177.0
80			182.0
90			189.0
95			195.2
FBP			205.3
End Point			205.3
Recovery			%(V/V)
Residue	1.0		
Loss	1.0		

TRUST | COMMITMENT | INTEGRITY



PRODUCT TECHNICAL DATA SHEET

WHITE SPIRIT 240 FBP

TEST	METHOD	UNIT	RESULT
Appearance	Visual	-	Clear and Bright
Flash Point	ASTM D 93	°C	30
Density @ 15°C	ASTM D 4052	Kg/l	0.7934
DISTILLATION			
IBP	ASTM D 86	°C	136
10			160
20			167
30			172
40			177
50			182
60			187
70			194
80			201
90			208
95			223
FBP			240

TRUST | COMMITMENT | INTEGRITY