



CERTIFICATE OF ANALYSIS

PRODUCT : BASE OIL N 70 (GR II) VIRGIN – ADNOC CARGO

PROPERTIES	TEST METHOD	UNIT	RESULTS
Appearance	VISUAL	-	Clear & Bright
Color	ASTM D 1500	-	L 0.5
Density @ 15°C	ASTM D 1298	Kg/L	0.862
Flash Point	ASTM D 93	°C	180
Kinetic Viscosity @ 40°C	ASTM D 445	cSt	15.2
Kinetic Viscosity @ 100°C	ASTM D 445	cSt	2.87

PACKAGE

- Bulk, Bulk in Flexi Containers, Bulk in ISO Tanks, Drums

TYPICAL APPLICATION

- Manufacture of Lubricants.

TRUST | COMMITMENT | INTEGRITY



LIBERTY TRADING INTERNATIONAL

TRUST | COMMITMENT | INTEGRITY

RECYCLED BASE OIL – SN 70

PROPERTIES	TEST METHOD	UNIT	PARAMETERS
Appearance	VISUAL	-	Clear & Bright
Density	ASTM D 1298	g/cm ³	0.83 – 0.84
Flash Point	ASTM D 93	°C	135 - 155
Kinetic Viscosity @ 100 ⁰ C	ASTM D 445	cSt	2.0 – 3.0
DISTILLATION		%wt	3.8722
IBP		°C	230 - 260
FBP	ASTM D 86	°C	370 - 380

PACKAGE

- Bulk, Bulk in Flexi Containers, Bulk in ISO Tanks, Drums

TYPICAL APPLICATION

- Manufacture of Lubricants.

TRUST | COMMITMENT | INTEGRITY



LIBERTY TRADING INTERNATIONAL

TRUST | COMMITMENT | INTEGRITY

RECYCLED BASE OIL – SN 150

PROPERTIES	TEST METHOD	UNIT	VALUE
Flash Point	ASTM D 92	°C	180
Viscosity @ 100°C	ASTM D 445	cSt	6 – 7-5
Pour Point	ASTM D 97	°C	-4
Density	ASTM D 1298	g/cm ³	0.875 ± 5
Color	ASTM D 1500	-	1.5 – 2.5

PACKAGE

- Bulk, Bulk in Flexi Containers, Bulk in ISO Tanks, Drums

TYPICAL APPLICATION

- Manufacturer of Lubricants.



TRUST | COMMITMENT | INTEGRITY